



energy experts

ESSO retail network
Mobil lubricants

Gasoline 95-E10

PROPERTY	UNIT	METHOD	LIMITS	
			min.	max.
Appearance		Visual	bright & clear	
Benzene content	% vol.	D 3606/EN 238 EN 12177/EN ISO 22854		1.00
Colour		Visual	undyed	
Copper Strip Corrosion, 50 °C, 3 h	rating	D 130/EN ISO 2160		1
Density, 15 °C	kg/m ³	D 4052/EN ISO 12185 EN ISO 3675	720.0	775.0
Distillation		D 86/EN ISO 3405		
Final Boiling Point	°C			210
Evap. at 70 °C	% vol.			
May, 1 - September, 30		a)	22.0	50.0
October, 1 - April, 30 ^{a)}			24.0	52.0
Evap. at 100 °C	% vol.		46.0	71.0
Evap. at 150 °C	% vol.		75.0	
Recovery	% vol.		96.0	
Residue	% vol.			2
Doctor Test or Mercaptan Sulphur	% mass	D 4952/ IP 30 D 3227/UOP 163	negative	
0.0010				
Existent gum content (solvent washed)	mg/100 ml	D 381/EN ISO 6246		5
Hydrocarbon type content	% vol.	D 1319/EN 15553/EN ISO 22854		
Aromatics				35.0
Olefins				18.0
Lead content	mg/l	D 3237/EN 237		5.0
Octane No., Motor Method ^{b)}		EN ISO 5163 ^{b)}	85.0	
Octane No., Research Method ^{b)}		EN ISO 5164 ^{b)}	95.0	
Odour			marketable	
Oxidation Stability	min	D 525/EN ISO 7536	360	
Oxygen content	% mass	EN 1601/EN 13132/EN ISO 22854		3.7
Oxygenates content	% vol.	EN 1601/EN 13132/EN ISO 22854		
Methanol				3.0
Ethanol				10.0
iso-Propyl alcohol				12.0
iso-Butyl alcohol				15.0
tert-Butyl alcohol				15.0
Ethers (5 or more C atoms)				22.0
Other oxygenates				15.0
Sulphur content	mg/kg	D 2622/EN ISO 20884 D 5453/EN ISO 20846 EN ISO 13032		10.0
Vapour Lock Index (VLI) ^{c)}		c)		
April, October				1200
Vapour Pressure (DVPE at 37.8°C) ^{d)}	kPa	D 5191/EN 13016-1 ^{d)}		
May, 1 - September, 30			45.0	60.0
October, 1 - April, 30 ^{a)}		a)	65.0	95.0

Specification meets the requirements of EN 228:2013.

- With reference to EN 228 (European specification for unleaded gasoline),

PETRO-CENTER S.A.

2, rue Jean Fischbach / Z.A. Am Bann / L-3372 Leudelange
Tél.: +352 26 37 27-1 / Fax: +352 26 37 27-900 / www.petro-center.lu

R.C. Luxembourg: B75045
T.V.A.: LU 18268456 IBLC / Autorisation N°: 91522